

SEMI-AUTOMATIC BOTTLE WASHER & FILL STATION


Our new semi-automatic wash-fill station has been engineered from the ground up and includes "hands free" operation and automatic "on/off" controls. The BWF-2's design is far superior compared to any other entry level washer/filler.

We guarantee it!



Easy to Operate

Large, touch-sensitive Start Buttons. Place your bottle on top of the wash nozzle... press the button and your wash cycle starts! The cycle stops after your pre-programmed timed cycle.



High Quality Pumps

All Precision Wash/Fill Sinks are equipped with 3/4hp SS pumps with Viton seals – built for high temperatures and long life. A built-in bypass system reduces pump wear with fewer starts.



Formed Bottle Cover

The lips around the wash nozzle on the wash/rinse/sanitize cover are designed for strength and will not mark or cut the bottle neck.



Drain Strainer Screen Protection

The 1 1/4" pump suction line is protected against large particles, dirt or labels from entering the pump. This protects your 5-year warranted pump.




Closed Cabinet Design

The closed cabinet keeps all components free from dirt, dust and water spillage as well as reducing operation noise. Made from 100% stainless steel.



Easy to adjust Fill Spouts

With a turn of the knob, the filling spouts adjust to any 1, 2, 3 or 5 gallon bottles you choose to fill.



Large Flow Solenoid Valve

All wash nozzles are equipped with a 24 volt solenoid which opens the flow to the wash nozzle. A 24 volt system is used for your safety.



Sanitized Cap Well

The sanitized cap well pre-heats and sanitizes caps



Semi-Automatic Operation

Wash, rinse and sanitize operations are automatic with a simple touch of the Start Button. They are easily adjusted from time periods of seconds to several minutes to meet your washing needs.

Other Features

- Construction is completely made of 300 Series stainless steel. It is easy to keep clean and has unsurpassed durability.
- Clear braided suction and return lines.
- 1500 watt heating element with adjustable thermostat on wash tank.
- 2000-watt heating element with adjustable thermostat on sanitize tank.
- Removable drip grate on fill area with drain connection.
- Tank fill faucet.
- Each system is tested prior to shipping.
- System comes partially assembled for easy, safe and economical shipping.

Installation Requirements

Electrical: one 1500w, one 2000w 220v heaters to be hardwired by your electrician.
 Plumbing: Domestic hot water supply and finished water supply.
 Motors (2): 3/4hp continuous duty 115/208/230 volt, 60 HZ, CSA, UL, CE
 Dimensions (approx.):
 Height – 38"
 Width – 76 1/2"
 Depth – 21 1/2"
 Weight – 235 lb.
 All Specifications are Subject to Change Without Notice

Warranty

Five Years on all stainless steel components and Pro Spec Pumps.
 One Year on all electrical and other components